CLAIMS

1. A non-austemper-treated spheroidal graphite cast iron obtainable without being subjected to an austemper treatment,

characterized in that the non-austemper-treated spheroidal graphite cast iron has a tensile strength of 650 - 850 MPa and an elongation of 7.0 - 14.5%.

A non-austemper-treated spheroidal graphite cast iron obtained without being subjected to an austemper treatment,

characterized in that V-notch material has a fatigue limit of 290 MPa or more.

- 3. A non-austemper-treated spheroidal graphite cast iron according to claim 1 or 2, wherein the non-austemper-treated spheroidal cast iron contains 0.05 0.45% by mass of Mn.
- 4. A non-austemper-treated spheroidal graphite cast iron according to claim 3, wherein the non-austemper-treated spheroidal cast iron contains 2.0 4.0% by mass of Ni.
- 5. A non-austemper-treated spheroidal graphite cast iron according to any one of claims 1-4, wherein the non-austemper-treated spheroidal cast iron has a Brinell hardness of 230-285 HB.
- 6. A non-austemper-treated spheroidal graphite cast iron according to any one of claims 1 4, wherein the non-austemper-treated spheroidal cast iron has a flank wear of 0.13 mm or/less in a cutting distance of 1.7 km.

 \mathcal{Q}_{0}

25

5

10

15

20

CLAIMS

1. A non-austemper-treated spheroidal graphite cast iron obtainable without being subjected to an austemper treatment,

characterized in that the non-austemper-treated spheroidal graphite cast iron has a tensile strength of 650 - 850 MPa and an elengation of 7.0 - 14.5%.

2. A non-austemper treated spheroidal graphite cast iron obtained without being subjected to an austemper treatment,

characterized in that V-notch material has a fatigue limit of 290 MPa or more.

- 3. A non-austemper-treated spheroidal graphite cast iron according to claim 1-or-2, wherein the non-austemper-treated spheroidal cast iron contains 0.05-0.45% by mass of Mn.
- 4. A non-austemper-treated spheroidal graphite cast iron according to claim 3, wherein the non-austemper-treated spheroidal east iron contains 2.0 4.0% by mass of Ni.
- 5. A non-austemper-treated spheroidal graphite cast iron according to any one of claims 1 4 claim 3, wherein the non-austemper-treated spheroidal cast iron has a Brinell hardness of 230 285 HB.
- 6. A non-austemper-treated spheroidal graphite cast iron according to any one of claims 1 4 claim 4, wherein the non-austemper-treated spheroidal cast iron has a flank wear of
- 25 0.13 mm or less in a cutting distance of 1.7 km.